

V O L V O



Volvo Articulated Haulers 39.0 t 57 km/h 476 hp

A40

Volvo Construction Equipment

A40

Setting the standard for off-road performance,
the best articulated hauler on the market just
got better.



The ultimate in performance, comfort and uptime

The Volvo A40 is designed for unbeatable off-road performance, operator comfort and maximum uptime. With features including Volvo drivetrain with Terrain Memory, intuitive operator interface, superior visibility, outstanding durability and reduced service costs, the A40 ensures maximum productivity, profitability and performance across the toughest of terrains.



Intuitive in-cab interface

- All essential in-cab information conveniently displayed on just two screens
- Interactive, integrated Volvo Co-Pilot display
- Dynamic instrument cluster in-front of steering wheel



A new level in operator comfort

- Easy access/egress
- Direct field of vision which exceeds industry standards
- Lighting and cameras
- Enhanced storage options
- Easy cleaning
- Range of suspension configurations



Unbeatable off-road performance

- Volvo Automatic Traction control (ATC) with Terrain Memory
- Automatic drive combinations including 6x6 and 6x4
- All-terrain bogie
- Hydro-mechanical steering
- Downhill speed control
- Dynamic and predictive gear selection
- Superior tipping stability



Reduction in service costs

- 250-hour greasing intervals
- Industry leading service access
- Remote monitoring and service alerts
- Enhanced electrical service center



Haulers and beyond

- Haul Assist with On-Board Weighing
- Connected Map and Performance Indicator
- Future proofed software architecture
- CareTrack telematics
- Operator Training Program
- Service contracts
- Optimal pass-matching with Volvo loading tools

Intuitive operator interface

Operators can stay in-the-know and focussed on the task at hand thanks to all essential in-cab information conveniently displayed on just two screens. The interactive, integrated Volvo Co-Pilot display offers easy control over essential functions such as media, camera settings, climate control and machine status. This is combined with the dynamic instrument cluster, positioned in front of the steering wheel, which provides essential vehicle data at a glance.

Volvo Automatic Traction Control with Terrain Memory

Experience superb fuel efficiency without compromising on power and performance thanks to the world-renowned Volvo drivetrain, including Terrain Memory. The intelligent function identifies and remembers slippery road segments to ensure optimized traction control and outstanding off-road mobility.

Enhanced visibility

Visibility is key to a safe, efficient and productive working day and thanks to the redesigned cab panels and wider wiper coverage, operators benefit from a direct field of vision which exceeds industry standards. Work lights activated via the integrated Volvo Co-Pilot are now located on the pillar, providing increased illumination to further optimize visibility.

Haul Assist with On-Board Weighing

Haul Assist, powered by the integrated Volvo Co-Pilot, is a set of tools designed to help you get even more productivity and efficiency from your Volvo Articulated Hauler. A key feature of Haul Assist is On-Board Weighing, which provides real-time payload information which can help to eliminate carry-back and overloading. The result is peak productivity, reduced fuel consumption and less machine wear.



Reduction in service costs

Reduce service costs thanks to simplified servicing, longer change intervals and easy component access. Benefit from industry leading greasing intervals of 250 hours for maximum uptime.

Unbeatable off-road performance

The A40 delivers unbeatable off-road performance in its class with features including the proven Volvo drivetrain, automatic drive combinations (including 100% differential locks), all-terrain bogie and hydro-mechanical steering for unmatched traction, stability and precision control. With Volvo Dynamic Drive, dynamic and predictive gear selection adapts to the operating conditions at hand, for improved comfort and fuel efficiency.



Volvo A40 in detail

Engine		
13 liter, 6-cylinder straight turbocharged diesel engine with 4 valves per cylinder, overhead camshaft and electronically controlled unit injectors. The engine has wet replaceable cylinder liners and replaceable valve guides and valve seats.		
Engine model	Volvo	D13F
Max power - SAE J1995 Gross	kW	350
	hp	476
at engine speed	r/min	1 800
Max torque - SAE J1995 Gross	Nm	2 525
	r/min	1 050
Displacement	l	12.8
Electrical system		
All cables, sockets and pins are identified. Cables are enclosed in plastic conduits and secured to main frame. Prewired for options. Connectors meet IP67 standard for water-proofing as necessary		
Voltage	V	24
Battery	V	2 x 12
Battery capacity	Ah	2 x 170
Alternator	kW/A	3.396 / 120
Starter motor	kW	9
Drivetrain		
Torque converter with built-in lock-up function. Transmission: Fully automatic Volvo PowerTronic planetary transmission with nine forward gears and three reverse gears. The transmission has the ability to skip gears for fast and accurate gear selection. Dropbox: Volvo-developed, in-line design with high ground clearance and 100% longitudinal "dog clutch" type differential lock. Axles: Heavy duty, purpose built Volvo design with fully floating axle shafts, planetary type hub reductions and 100% dog clutch type diff-lock. Automatic Traction Control system (ATC).		
Torque converter		2.1:1
Transmission	Volvo	PT 2529
Dropbox	Volvo	IL2 ATC
Axles	Volvo	ARB H40/45/50

Brake system		
Fully hydraulic, wet multiple disc brakes with enclosed, forced oil-cooled multiple discs on all wheels. Two circuit brake system. Complies with ISO 3450 at total machine weight. Circuit division: One circuit for front axle and one for bogie axles. Parking brake: Spring-applied disc brake on the propeller shaft, designed to hold a loaded machine on a grade of up to 18%. When the parking brake is applied, the longitudinal differential is locked. Retarder: Service brake retarder function and Volvo Engine Brake (VEB)		
Steering System		
Hydro-mechanical articulated steering, self compensating design. Two double-acting steering cylinders. Steering angle: 3,4 steering wheel turns lock-to-lock, $\pm 45^\circ$. Steering system: including secondary steering fulfills ISO 5010.		
Chassis		
Frames: box type, heavy duty. High strength steel, robot welded. Rotating hitch: 100% maintenance free, fully sealed, with permanently greased tapered roller bearings		
Cab		
Mounted on rubber pads. Ergonomically designed. Unobstructed wide angle forward view. Operator centrally positioned above the front axle. ergonomically positioned controls. Electronic controlled climate unit with automatic controlled temperature and functionality with high thermal comfort and clean air. The controls, switches, and instruments in the cab of the hauler machine are designed with a strong focus on ergonomics and the appropriateness of information content for the operator. These elements are strategically placed to provide operators with intuitive access to critical functions while minimizing distractions. Ergonomics play a pivotal role in the design, ensuring that controls are within easy reach and that their layout minimizes operator fatigue during long shifts. The primary 8" display, positioned directly in front of the operator, serves as a central hub for monitoring vital machine functions, displaying information in a clear and organized manner. The 12" secondary display complements this by enhancing situational awareness. The information presented on these displays is carefully curated to deliver the most pertinent data, alerts, and notifications, enabling operators to make informed decisions swiftly and accurately. Safety: ROPS/FOPS standards approved according to ISO3471, SAE J1040 / ISO3449, SAE J231.		
Sound level in cab (ISO 6396) - L _{PA}	dB	72
External sound level (ISO 6395) - L _{WA}	dB	112
Internal sound level with sound kit: 70 dB(A) External sound level with sound kit: 110 dB(A)		

Hydraulic system		
Four variable displacement piston pumps driven by the flywheel PTO Two load-sensing used for steering and tipping and two electrical controlled used for fan, brake cooling and brake power supply. One ground-dependent piston pump for secondary steering mounted on the dropbox. Two return oil filters with magnetic cores provide effective oil filtration		
System max working pressure	MPa	28
Dumping System		
Patented Load and Dump Brake. Dumping Cylinders: two single stage double acting cylinders.		
Tipping angle	°	69
Tipping time with load	s	12
Lowering time	s	10
Body		
Plate thickness		
Front	mm	8
Sides	mm	11
Bottom	mm	14
Chute	mm	16
Material HB450 steel		
Yield strength	N/mm ²	1 150
Tensile strength	N/mm ²	1 350

Load Capacity		
Standard Body		
Load capacity	kg	39 000
Body, struck	m ³	18.7
Body, heaped 2:1	m ³	24
With overhung tailgate		
Body, struck	m ³	19.1
Body, heaped 2:1	m ³	25.1
Suspension		
Front suspension: Three point suspension consisting of a-stay fitted to the frame structure by a spherical rubber bushing, shock absorbers with accumulators and cross stays.		
Reat suspension: 3-point bogie beam suspension consisting of a straddle-mounted bogie beam with maintenance free rubber bearings, flexible rubber pads, cross stays and a-stay		

Specifications

REFILL CAPACITIES

		A40J
Crankcase	l	50
Fuel tank	l	563
Cooling system	l	44
Brake cooling system	l	207
Transmission	l	43
Dropbox	l	9
Axles, front/bogie	l	26/53
Hydraulic tank	l	199

SPEED

		A40J
Forward		
1	km/h	5.8
2	km/h	8.5
3	km/h	10.4
4	km/h	15.0
5	km/h	21.6
6	km/h	27.3
7	km/h	36.1
8	km/h	47.8
9	km/h	57.0
Reverse		
1	km/h	6.5
2	km/h	9.4
3	km/h	18.0

OPERATING WEIGHT UNLOADED

		A40J
Tires		29.5R25*
Front	kg	16 960
Rear	kg	14 340
Total	kg	31 300
Payload	kg	39 000

Operating weight includes all fluids and operator

*) A40J with tires 875/65R29, add 300 kg /axle





TOTAL WEIGHT

		A40J
Tires		29.5R25*
Front	kg	21 580
Rear	kg	48 630
Total	kg	70 210

*) A40J with tires 875/65R29, add 300 kg /axle

GROUND PRESSURE

		A40J	
Tires		29.5R25	875/65R29
Unloaded			
Front	kPa	122	102
Rear	kPa	51	44
Loaded			
Front	kPa	155	130
Rear	kPa	174	145



DIMENSIONS

Pos	Unit	A40J
A	mm	11 261
A ₁	mm	5 459
A ₂	mm	6 418
B	mm	5 861
C	mm	3 626
C ₁	mm	1 819
D	mm	3 084
D ₁	mm	2 941
E	mm	1 277
F	mm	4 628
G	mm	1 940
H	mm	1 609
I	mm	494
J	mm	3 142
K	mm	2 434
L	mm	951
M	mm	7 400
N	mm	9 144
N ₁	mm	4 428
O	mm	3 324

DIMENSIONS

Pos	Unit	A40J
P	mm	3 118
Q	mm	2 820
R	mm	652
R ₁	mm	744
S	mm	2 651
T	mm	3 458
U	mm	3 574
V	mm	2 636
W	mm	3 401
X	mm	583
X ₁	mm	688
X ₂	mm	821
Y	mm	2 636
Z	mm	3 400
a ₁	°	25,3
a ₂	°	69
a ₃	°	45

A40J: Unloaded machine with 29.5R25

Equipment

STANDARD EQUIPMENT

Cab/Operator environment

Operator seat with head restraint (air suspended and heated)
Electronic Climate Control
Cup holder / storage tray
Cell phone holder
Instructor seat with seat belt
Overhead console for CC Radio, Tachograph, etc.
Air suspended / heated operator seat
Sliding window
Cooled / Heated storage box
Front sun visor
Tilt/telescopic steering wheel
Loud speakers (4)
Dynamic instrument cluster and integrated Co-Pilot
Automatic pre-start checks
Troubleshooting diagnostics

Engine

Preheater for easier cold starts
VEB (exhaust retarder EPG + compression brake)

Wheels and tires

29.5R25

Drivetrain

6x4 and 6x6 Automatic Traction Control (ATC)
Dog clutch type 100% diff-locks in all axles
Cruise Control
Dropbox with longitudinal diff-lock
Torque converter with automatic lock-up in all gears

Electrical system

Battery disconnect switch
Electrical Interface
Charging studs
Power outlets
USB-C 2.0 (2)
USB-A 3.0 (1)
24V (2)
Exterior and Interior lights (all LED)

Brake system

Two circuit, fully hydraulic, wet discs on all axles (externally cooled)
Down Hill Speed Control
Hill assist
Load & Dump Brake
Retarder pedal
Parking brake on propeller shaft

STANDARD EQUIPMENT

Dumping System

Body prepared for exhaust heating and optional equipment
--

Safety and security

Anti-slip steps and platforms with handrails
Dump body lock
Steering joint lock
Harness anchor points
Rear-view mirrors
Retractable 3-inch 2-point safety belt
ROPS / FOPS protected Care Cab
Secondary steering
Dump support system
Positioning indicators (front and rear)
Entrance camera

Service and Maintenance

Grouped service points and filters
Electrical fuel priming pump
Prepared for fast fueling equipment
Ambient and service lights (LED)
Electrical engine hood
Belly plate with integrated service hatches
Drainage hoses
Tool box
Front service ladder

OPTIONAL EQUIPMENT
Engine
Air filter, heavy duty
Engine heater, electric
Engine heater, diesel
Engine shutdown timer
External emergency engine stop
Operator Environment
Noise reduction kit (fulfils 2000/14/EC)
Anchorage, operator's manual
Cab heating / ventilation timer
Cable kit, for cab heater
Cab air filter (Asbestos dust protection)
Cab air filter (Carbon)
Rear view mirrors, adjustable, el.heated
Sun blinds, side windows
Universal key
Premium operator seat with head restraint (air suspended, cooled / heated), 2-point belt
Premium operator seat with head restraint (air suspended, cooled / heated), 3-point belt
Armrest for operator seat
Hands-free microphone
Radio AM / FM / DAB
Wheels and tires
875/65R29
Drivetrain
Long haul kit, dropbox cooling
Speed limiter (25/30 km/h)
Electrical system
Warning beacon, LED
Seatbelt indicator, external
Working lights front and rear, LED
Rear view camera
Front view camera
Reverse alarm
PDS interface, Safemine
Tire Pressure Monitoring System
Suspension
Rubber front suspension
Hydraulic front suspension

OPTIONAL EQUIPMENT
Dumping System
Body exhaust heating
Front spillguard, extra
Side extension, 200 mm
Side extension, 400 mm
Side extension, light material
Tailgate, overhung, wire-operated
Tailgate, overhung, linkage-operated
Tailgate, underhung
Wear plates, 450 HB
Wear plates heavy duty, 450 HB
Safety and security
Fire suppression system
Warning triangle
First aid kit and fire extinguisher
Fire extinguisher, external
Wheel chocks
Service and maintenance
Auto Lube system
Centralized greasing
Tool kit
Other
Arctic oil kit
Fast fuelling system
Jump start connector, ISO-type

Our Branches



Albany

17 Charles St
Milpara, WA, 6330
Tel 08 9841 1249

Alice Springs

12 Cameron Street
Braitling, NT 0870
Tel 08 8959 0500

Bibra Lake

1/1 Discovery Drive
Perth, WA, 6163
Tel 08 9359 7480

Brisbane

32-36 Colebard St East
Acacia Ridge, QLD 4110
Tel 07 3276 3700

Bunbury

10 Kerr Rd
Picton East, WA 6229
Tel 08 9722 8100

Burnie

44 Main Rd
Wivenhoe, TAS 7320
Tel 03 6431 7833

Canberra

40 Yass Road
Queanbeyan, NSW 2620
Tel 02 4648 9651

Dandenong

46 Greens Rd
Dandenong, VIC, 3175
Tel 03 9767 8000

Darwin

1 Toupein Rd
Yarrawonga, NT, 0830
Tel 08 8935 9100

Forrestfield

787 Abernethy Road
Forrestfield, WA, 6058
Tel 08 9359 7400

Geelong

106 St Georges Rd
Corio, VIC 3214
Tel 03 6262 6220

Geraldton

383 Edward Rd
Meru, WA, 6530
Tel 08 9960 8000

Guildford

52 Great Eastern Highway
South Guildford, WA, 6055
Tel 08 9277 0111

Hobart

56 Crooked Billet Dr
Bridgewater, TAS, 7030
Tel 03 6262 6200

Kalgoorlie

85 Craig Rd
Kalgoorlie, WA, 6430
Tel 08 9080 0500

Launceston

401 Westbury Rd
Prospect Vale, TAS, 7250
Tel 03 6345 4100

Mackay

Connors Rd
Paget, QLD, 4740
Tel 04847 7300

Melbourne

210 Northbourne Rd
Campbellfield, VIC, 3061
Tel 03 9305 9900

National

54 Great Eastern Highway
South Guildford, WA, 6055
Tel 08 9478 0000

Newcastle

2 Glenwood Dr
Thornton, NSW, 2322
Tel 02 4926 9600

Sydney

10 Anzac Ave
Smeaton Grange, NSW, 2567
Tel 02 4648 9600

Port Hedland

17 Pinnacles St
Wedgedield, WA, 6721
Tel 08 9140 0200

Rockhampton

1 Featherstone Street,
Parkhurst, QLD, 4702
Tel 07 4847 7330

Wodonga

2A Stead St
Wodonga, VIC, 3690
Tel 02 6092 2200